

Lembar data produk

Spesifikasi

Comb busbar, Easy9 XP, 3P, 63 A, 57 modules



EZ9XPH357

Main

Range	Easy9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	57

Complementary

Number of ways	19 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	54 mm
Insulation	Insulated
Device presentation	Cutable
Provided equipment	2 end piece
[Ie] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC 50 Hz Ph/N 400 V AC 50 Hz Ph/Ph
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-1
Mounting location	Top on tunnel type terminals
9 mm pitches	114
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Easy9 XP

Environment

Standards	IEC 60439-1 IEC 60664
Fire resistance	850 °C (30 s) conforming to IEC 60695-2-1

Pollution degree	2
------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	428.0 g
Package 1 Height	1.5 cm
Package 1 Width	2.5 cm
Package 1 Length	101.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	270
Package 2 Weight	136.2 kg
Package 2 Height	53.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	2.35 kg
Package 3 Height	5.0 cm
Package 3 Width	8.5 cm
Package 3 Length	106.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------