



Miniature circuit breaker 400 V 6kA, 2-pole, C, 32 A Circuit breaker 400 V 6kA, 2-pole, C, 32 A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
design of pole	2P
tripping characteristic class	C
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (U _i)	440 V
<ul style="list-style-type: none"> with multi-phase operation at AC rated value 	440 V
Supply voltage	
supply voltage at AC rated value	400 V
value range of the supply voltage frequency	50/60 Hz
operating voltage	440 V
<ul style="list-style-type: none"> with multi-phase operation at AC maximum at DC rated value maximum 	72 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	6 kA
<ul style="list-style-type: none"> according to EN 60898 rated value 	6 kA
energy limitation class	3
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	4.6 W
Current	
operational current	32 A
<ul style="list-style-type: none"> at 30 °C rated value at 40 °C rated value at 45 °C rated value at 50 °C rated value at 55 °C rated value at AC rated value 	30.18 A 29.22 A 28.24 A 27.22 A 32 A
suitability for operation	Residential buildings/infrastructure
Product details	
product feature	Yes
<ul style="list-style-type: none"> halogen-free 	Yes

• sealable	Yes
• silicon-free	Yes
product extension installable supplementary devices	Yes

Connections

connectable conductor cross-section solid	
• minimum	0.75 mm ²
• maximum	25 mm ²
connectable conductor cross-section stranded	
• minimum	0.75 mm ²
• maximum	25 mm ²
connectable conductor cross-section finely stranded with core end processing	
• minimum	0.75 mm ²
• maximum	25 mm ²
tightening torque with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m

Mechanical Design

height	90 mm
width	36 mm
depth	76 mm
installation depth	70 mm
number of modular width units	2
mounting position	any

Environmental conditions

vibration resistance according to IEC 60068-2-6	50 m/s ² at 25 to 150 Hz
ambient temperature during operation	
• minimum	-25 °C
• maximum	45 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	75 °C

Certificates

reference code	
• according to EN 61346-2	F
• according to IEC 81346-2	F

General Product Approval

EMC

Declaration of Conformity



[Confirmation](#)



other

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6232-7CC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL6232-7CC>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6232-7CC

CAx-Online-Generator

<http://www.siemens.com/cax>



