
SIEMENS

Data sheet

3WL9111-0AG02-0AA0

accessories circuit breaker 3WL aux.switch block 2NO+0NC



Model		
product brand name	SENTRON	
product designation	Auxiliary contacts for switch position	
design of the product	Accessories	
General technical data		
degree of pollution	3	
Voltage		
surge voltage resistance rated value	4 kV	
Supply voltage		
operating voltage		
 at AC at 50 Hz rated value maximum 	500 V	
 at DC rated value maximum 	500 V	
Current		
operational current		
 at AC-12 at 110 V rated value 	10 A	
 at AC-12 at 24 V rated value 	10 A	
 at AC-12 at 48 V rated value 	10 A	
 at AC-12 at 400 V rated value 	10 A	
 at AC-12 at 230 V rated value 	10 A	
 at AC-15 at 24 V rated value 	4 A	
 at AC-15 at 48 V rated value 	4 A	
 at AC-15 at 110 V rated value 	4 A	
 at AC-15 at 230 V rated value 	4 A	
 at AC-15 at 400 V rated value 	3 A	
 at DC-12 at 230 V rated value 	1 A	
 at DC-13 at 220 V rated value 	0.4 A	
 at DC-12 at 110 V rated value 	3.5 A	
 at DC-12 at 48 V rated value 	8 A	
 at DC-13 at 110 V rated value 	1.2 A	
 at DC-13 at 48 V rated value 	4 A	
 at DC-12 at 24 V rated value 	10 A	
 at DC-13 at 24 V rated value 	8 A	
General Product Approval EMC	Declaration of Conformity	Test Certificates
		<u>Miscellaneous</u>

Miscellaneous	Environmental Con-	Miscellaneous
	firmations	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AG02-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AG02-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0AG02-0AA0

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications