Product datasheet

Specifications



20A 250V 1 Gang 2 Way Double Pole Switch with Neon and Earth

KB31D20NE_2

Discontinued on: 21 February 2017

1 End-of-service on: 13 March 2017

(!) Discontinued

Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device presentation	Complete mechanism

Complementary	
Switch function	Double 1-way with earth
Actuator	Rocker
Pilot light	Neon indicator lamp
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	20 A at 250 V AC, inductive 20 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Terminal identifier	L2 N2 L1 N1
Tightening torque	0.4 N.m

Clamping connection capacity	<= 2.5 mm ²
Width	86 mm
Height	86 mm
Environment	
Standards	SS 227 IEC 60669-1 MS IEC 60669-1
Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use
Packing Units	
Package 1 Weight	83.750 g
Package 1 Height	1.000 mm
Package 1 Width	1.000 mm
Package 1 Length	1.000 mm
Contractual warranty	

Recommended replacement(s)

18 months

Warranty