

# Product data sheet

Specifications



## 20A Vertical Dolly Double Pole Switch with White LED, Grey Silver

E3031VD20\_EBGS

### Main

Range	Neo
Product or component type	Control switch
Wiring device mounting	Surface Flush
Switch function	2-pole
Switch application	Switch
Load type	Inductive Fluorescent lamp Resistive
Bulb type	LED (blue)
Colour tint	Grey silver

### Complementary

Rated current	20 A at 250 V AC 50 Hz
Number of gangs	1 gang vertical
Material	Brass: metal parts Polycarbonate: plastic part Steel: metal parts
Clamping connection capacity	1 x 2.5...1 x 6 mm <sup>2</sup> for solid cable(s) 1 x 2.5...1 x 6 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	86 mm
Height	86 mm
Embedding depth	19.7 mm
Depth	8 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	GB 16915.1 EN 60669-1 IEC 60669-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	117.425 g
Package 1 Height	3.8 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	1600
Package 2 Weight	187880.0 g
Package 2 Height	86 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Weight	939.0 g
Package 3 Height	15 cm
Package 3 Width	19 cm
Package 3 Length	8 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)