

CAT. N° 4 160 96



### 3-POLE CONTACTORS CTX<sup>3</sup> 22 - 12 A 230 V~ - 1 NO + 1 NC - SCREW TERMINALS

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,371
Weight (g)	343,00

#### Product characteristics

##### CTX<sup>3</sup> 22

- With integrated auxiliary contacts
- Power terminals: screw terminals

##### 12 A (AC3) - 25 A (AC1)

- Screw terminals
- 3-phase motor 400/415 V : 5.5 kW
- Control Voltage : 230 V~
- Integrated auxiliary contacts : 1 NO + 1 NC

#### General characteristics

##### 3-pole contactors CTX<sup>3</sup> - 9 A to 100 A industrial contactors

- Conform to IEC 60947-1, IEC 60947-4-1
- Can be equipped with RTX<sup>3</sup> thermal relays add-on auxiliary contact blocks, time delay blocks, capacitor switching units and CTX<sup>3</sup> interlocking

#### Documentation



##### Catalogue pages & additional information

- [Technical page \(p.186-187\)](#)
- [Description page \(p.190\)](#)
- [Technical page \(p.196-197\)](#)
- [3-pole contactors CTX<sup>3</sup>](#)



##### Installation & technical data

- [F01989EN-06](#)



##### Installation instructions & related documents

- [LE07229AB](#)



##### Environmental product profile

- [LGRP-00209-V01](#)