

CAT. N° 4 162 69



3-POLE CONTACTORS CTX³ 150 - 150 A - 400-440 V~ - 2 NO + 2 NC -SCREW TERMINALS

Pack (number of units)	1
Volume (dm ³)	3,009
Weight (g)	2 236,00

Product characteristics

CTX³ 150

- With integrated auxiliary contacts

150 A (AC3) - 210 A (AC1)

- Screw terminals
- 3-phase motor 400/415 V : 75 kW
- Control Voltage : 400-440 V~
- Integrated auxiliary contacts : 2 NO + 2 NC

General characteristics

3-pole contactors CTX³ - 130 A to 800 A industrial contactors

- Conform to IEC 60947-1, IEC 60947-4-1
- Can be equipped with RTX³ thermal relays add-on auxiliary contact blocks, time delay blocks (except CTX³ 225/400/800) and CTX³ interlocking

Documentation



Catalogue pages & additional information

- [Technical page \(p.186-187\)](#)
- [Description page \(p.191\)](#)
- [Technical page \(p.196-197\)](#)
- [3-pole contactors CTX³](#)



Installation & technical data

- [F01989EN-06](#)



Installation instructions & related documents

- [LE07229AB](#)



Environmental product profile

- [LGRP-00209-V01](#)