

CAT. N° 4 161 16



3-POLE CONTACTORS CTX³ 22 - 22 A 230 V~ - 1 NO + 1 NC - SCREW TERMINALS

Pack (number of units)	1
Volume (dm ³)	0,391
Weight (g)	361,00

Product characteristics

CTX³ 22

- With integrated auxiliary contacts
- Power terminals: screw terminals

22 A (AC3) - 40 A (AC1)

- Screw terminals
- 3-phase motor 400/415 V : 11 kW
- Control Voltage : 230 V~
- Integrated auxiliary contacts : 1 NO + 1 NC

General characteristics

3-pole contactors CTX³ - 9 A to 100 A industrial contactors

- Conform to IEC 60947-1, IEC 60947-4-1
- Can be equipped with RTX³ thermal relays add-on auxiliary contact blocks, time delay blocks, capacitor switching units and CTX³ interlocking

Documentation

Catalogue pages & additional information

- [Technical page \(p.186-187\)](#)
- [Description page \(p.190\)](#)
- [Technical page \(p.196-197\)](#)
- [3-pole contactors CTX³](#)

Installation & technical data

- [F01989EN-06](#)

Installation instructions & related documents

- [LE07229AB](#)

Environmental product profile

- [LGRP-00209-V01](#)