



Model			GWC09AGAXA-K3NNA1C	GWC12AGBXA-K3NNA1A	GWC18AGCXD-K3NNA1A	GWC24AGDXD-K3NNA1C
Function			Cooling	Cooling	Cooling	Cooling
Cooling Capacity	Cooling	Btu/h	9213	11000	16907	21000
	Heating	Btu/h	/	/	/	/
EER		W/W	3	2.69	3.61	3.42
Power Supply		Ph,V,Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz
Power Input	Cooling	W	900	1200	1370	1800
Rated Current	Cooling	A	6.8	8.9	13	14.00
Air Flow Volume	Indoor	m ³ /h	500/460/380/250	590/520/400/280	680/660/620/490	950/850/750/700/670/630/550
Indoor Unit						
Sound Pressure Level	Indoor	dB (A)	39/37/33/26	41/37/35/30	41/40/38/35	46/43/40/38/35/33/32
Outline Dimension	WxHxD	mm	704x260x185	779x260x185	825x293x196	982x311x221
Package Dimension	WxHxD	mm	753x332x258	828x332x258	875x365x268	1044x385x297
Net Weight/Gross Weight	Indoor	kg	7.5/9	8/9.5	10.5/12.5	13.7/16
Outdoor Unit						
Sound Pressure Level	Outdoor	dB (A)	49	52	55	57
Piping Connection	Gas	mm	φ9.52	φ9.52	φ12	φ12
		in.	3/8	3/8	1/2	1/2
	Liquid	mm	φ6	φ6	φ6	φ6
		in.	1/4	1/4	1/4	1/4
Outline Dimension	WxHxD	mm	710x450x293	710x450x293	802x555x350	802x555x350
Package Dimension	WxHxD	mm	764x525x330	764x525x330	872x620x398	872x398x620
Net Weight/Gross Weight	Outdoor	kg	24/26	24/26	35/37.5	37/39.5