

Model			GWC09AGB-K6DNA4G	GWC12AGB-K6DNA1B	GWC18AGD-K6DNA1H	GWC24ALEXE-K6DNA1A
Function			Cooling	Cooling	Cooling	Cooling
Cooling Capacity	Cooling	Btu/h	9000	12112	16377	22008
	Heating	Btu/h	/	/	/	/
EER		W/W	3.71	3.114	3.2	3.36
Power Supply		Ph, V, Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz
Power Input	Cooling	W	712	1140	1500	1920
Rated Current	Cooling	A	5.5	7	8.6	10.5
Air Flow Volume	Indoor	m ³ /h	570/520/480/410/340/300/280	590/520/480/400/350/320/280	950/800/650/540/500	1250/1050/850/600
Indoor Unit						
Sound Pressure Level	Indoor	dB (A)	39/37/36/34/30/25/24	41/37/35/33/30/27/25	43/39/34/31/29	51/47/42/37
Outline Dimension	WxHxD	mm	779×260×185	779×260×185	982×311×221	1081×325×248
Package Dimension	WxHxD	mm	828×332×258	828×332×258	1044×385×297	1137×407×334
Net Weight/Gross Weight	Indoor	kg	8.5/10	8.5/10	13.5/16	17/20
Outdoor Unit						
Sound Pressure Level	Outdoor	dB (A)	50	49	51	59
Piping Connection	Gas	mm	φ9.52	φ9.52	φ9.52	φ16
		in.	3/8	3/8	3/8	5/8
	Liquid	mm	φ6	φ6	φ6	φ6
		in.	1/4	1/4	1/4	1/4
Outline Dimension	WxHxD	mm	732×550×330	732×555×330	732×550×330	873X555X376
Package Dimension	WxHxD	mm	792×615×393	794×615x376	794×615x376	951X431X620
Net Weight/Gross Weight	Outdoor	kg	24/26.5	23/25.5	24/26.5	33.5/36.5