

Model			GVC18AM-K6NNC7B	GVC24AM-K6NNC7B	GVC36ALXH-K6NNC7B	GVC48ALXH-M6NNC7B
Function			Cooling	Cooling	Cooling	Cooling
Cooling Capacity	Cooling	Btu/h	18000	24000	32415	42000
	Heating	Btu/h	/	/	/	/
EER		W/W	3.72	3.40	3.88	3.42
Power Supply		Ph, V, Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	1Ph,220-240V, 50Hz	3Ph,380V, 50Hz
Power Input	Cooling	W	1420	2060	2450	3600
Rated Current	Cooling	A	10.00	16.0	16.0	11.0
Air Flow Volume	Indoor	m ³ /h	970/830/720/610	1000/850/730/650	1900/1700/1550/1400	1900/1700/1550/1400
Indoor Unit						
Sound Pressure Level	Indoor	dB (A)	44/41/39/37	45/43/41/37	53/50/48/45	53/50/48/45
Outline Dimension	WxHxD	mm	485×1720×321	507×1770×320	587×1882×394	587×1882×394
Package Dimension	WxHxD	mm	618×1928×430	623×1988×440	738×2153×545	738×2153×545
Net Weight/Gross Weight	Indoor	kg	36/49.5	38/50	55/77.5	52/74.5
Outdoor Unit						
Sound Pressure Level	Outdoor	dB (A)	54	54	60	61
Piping Connection	Gas	mm	φ12	φ12	φ16	φ16
		inches	1/2	1/2	5/8	5/8
	Liquid	mm	φ6	φ6	φ6	φ6
		inches	1/4	1/4	1/4	1/4
Outline Dimension	WxHxD	mm	802×555×350	873×555×376	1000×746×427	1000×746×427
Package Dimension	WxHxD	mm	872×620×398	951×620×431	1080×810×483	1080×810×483
Net Weight/Gross Weight	Outdoor	kg	39/41.5	45.5/48.5	63/68	68/73