

Model			GVH24AN-S6DND9A
Function			cooling/Heating
Capacity	Cooling	Btu/h	24601
	Heating	Btu/h	32755
EER/COP		W/W	3.31
Power Supply		Ph,V,Hz	1Ph,220~240V,50/60Hz
Power Input	Cooling	W	2180
	Heating	W	3050
Rated Current	Cooling	A	9.5
	Heating	A	13.4
Airflow Volume	Indoor	m³/h(SH/H/M/L)	1200/1000/830/660/560/450
Indoor Unit			
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	46/43/40/39/36/34/29
Outline Dimension	WxHxD	mm	422×1825×472
Package Dimension	WxHxD	mm	507×2078×564
Net Weight/Gross Weight	Indoor	Kg	39/52.5
Outdoor Unit			
Sound Pressure Level	Outdoor	dB(A)	60
Outline Dimension	WxHxD	mm	965×700×396
Package Dimension	WxHxD	mm	1029×750×458
Piping Connection	Liquid	mm	φ6
		in.	1/4
	Gas	mm	φ12
		in.	1/2
Net Weight/Gross Weight	Outdoor	Kg	54/58.5
Loading Quantity	40'GP	sets	60
	40'HQ	sets	70