

Cassette Type Data

Model	Indoor Unit		GULD125T1/A1-S	GULD140T1/A-S	GULD160T1/A-S
	Outdoor Unit		GULD125W1/NhA-S	GULD140W1/NhA-S	GULD160W1/NhA-S
Rated Cooling Capacity		kW	12.50	14.01	15.40
Power Input		kW	4.40	5.20	5.40
EER		W/W	2.84	2.69	2.85
Indoor Unit			GULD125T1/A1-S	GULD140T1/A-S	GULD160T1/A-S
Power Supply			220-240V ~50/60Hz		
Air Volume (SH/H/M/L)		m ³ /h	2100/1900/1700/1500	2100/1900/1700/1500	2400/2200/1900/1600
Sound Pressure Level(SH/H/M/L)		dB(A)	52/50/47/45		
Connection Pipe	Liquid Pipe	in.	Φ3/8		
	Gas Pipe	in.	Φ5/8		
	Water Pipe	mm	Φ25×1.50		
Dimensions (W×D×H)	Outline	mm	840×840×240	840×840×240	840×840×290
	Package	mm	933×903×272	933×903×272	933×903×335
Weight	Net/Gross	kg	23.0/29.0	23.0/29.0	25.0/32.0
Panel Dimensions (W×D×H)	Outline	mm	950×950×52		
	Packaged	mm	1033×1020×110		
Panel Weight	Net/Gross	kg	6.0/9.5		
Outdoor Unit			GULD125W1/NhA-S	GULD140W1/NhA-S	GULD160W1/NhA-S
Power Supply			220-240V ~50/60Hz		
Air Volume		m ³ /h	5200		
Sound Pressure Level		dB(A)	58	58	60
Connection Pipe	Liquid Pipe	in.	Φ3/8		
	Gas Pipe	in.	Φ5/8		
Dimensions (W×D×H)	Outline	mm	940×370×820		
	Package	mm	1093×497×885		
Weight	Net/Gross	kg	69.0/76.0	69.0/76.0	72.0/79.0