

Floor Ceiling Type Data

Model	Indoor Unit		GULD50ZD1/A-S	GULD71ZD1/A-S	GULD100ZD1/A-S
	Outdoor Unit		GULD50W1/NhA-S	GULD71W1/NhA-S	GULD100W1/NhA-S
Rated Cooling Capacity		kW	5.30	7.10	10.50
Power Input		kW	1.56	2.05	3.28
EER		W/W	3.40	3.46	3.20
Indoor Unit			GULD50ZD1/A-S	GULD71ZD1/A-S	GULD100ZD1/A-S
Power Supply			220-240V ~50/60Hz		
Air Volume (SH/H/M/L)		m ³ /h	1000/900/800/700	1200/1100/1000/800	1800/1600/1400/1200
Sound Pressure Level(SH/H/M/L)		dB(A)	45/43/41/39	48/46/45/43	48/45/43/41
Connection Pipe	Liquid Pipe	in.	Φ1/4	Φ3/8	Φ3/8
	Gas Pipe	in.	Φ1/2	Φ5/8	Φ5/8
	Water Pipe	mm	Φ17×1.50		
Dimensions (W×D×H)	Outline	mm	870×665×235	870×665×235	1200×665×235
	Package	mm	973×770×300	973×770×300	1303×770×300
Weight	Net/Gross	kg	25.0/29.0	25.0/29.0	32.0/37.0
Outdoor Unit			GULD50W1/NhA-S	GULD71W1/NhA-S	GULD100W1/NhA-S
Power Supply			220-240V ~50/60Hz		
Air Volume		m ³ /h	1800	3600	3600
Sound Pressure Level		dB(A)	48	56	54
Connection Pipe	Liquid Pipe	in.	Φ1/4	Φ3/8	Φ3/8
	Gas Pipe	in.	Φ1/2	Φ5/8	Φ5/8
Dimensions (W×D×H)	Outline	mm	675×285×553	889×340×660	889×340×660
	Package	mm	794×376×605	1032×456×730	1032×456×730
Weight	Net/Gross	kg	24.5/27.0	41.5/45.0	44.0/47.5