

Floor Ceiling Type Data

Model	Indoor Unit		GULD125ZD1/A1-S	GULD140ZD1/A-S	GULD160ZD1/A-S
	Outdoor Unit		GULD125W1/NhA-S	GULD140W1/NhA-S	GULD160W1/NhA-S
Rated Cooling Capacity	kW		12.50	14.01	16.00
Power Input	kW		3.80	4.70	5.40
EER	W/W		3.29	2.98	2.96
Indoor Unit			GULD125ZD1/A1-S	GULD140ZD1/A-S	GULD160ZD1/A-S
Power Supply			220-240V ~50/60Hz		
Air Volume (SH/H/M/L)	m ³ /h		2300/2000/1700/1400	2300/2000/1700/1400	2600/2300/2000/1600
Sound Pressure Level(SH/H/M/L)	dB(A)		49/46/42/39	49/46/42/39	52/49/46/42
Connection Pipe	Liquid Pipe	in.	Φ3/8		
	Gas Pipe	in.	Φ5/8		
	Water Pipe	mm	Φ17×1.50		
Dimensions (W×D×H)	Outline	mm	1570×665×235		
	Package	mm	1669×770×300		
Weight	Net/Gross	kg	40.0/47.0	40.0/47.0	42.0/49.0
Outdoor Unit			GULD125W1/NhA-S	GULD140W1/NhA-S	GULD160W1/NhA-S
Power Supply			220-240V ~50/60Hz		
Air Volume	m ³ /h		5200		
Sound Pressure Level	dB(A)		58	58	60
Connection Pipe	Liquid Pipe	in.	Φ3/8		
	Gas Pipe	in.	Φ5/8		
Dimensions (W×D×H)	Outline	mm	940×370×820		
	Package	mm	1093×497×885		
Weight	Net/Gross	kg	69.0/76.0	69.0/76.0	72.0/79.0