

Easy9 surge arrester - 3P + N - 400 V - 20000 A

EZ9L33720

viain	۱
-------	---

Range of product	Easy9
Product or component type	Surge arrester
Device short name	Easy9 SPD
Poles	3P + N
Remote signalling	Without
Surge arrester type	Electrical distribution network
Earthing system	TN-S TT
Disconnector device type	Associated circuit breaker at 400 V

Complementary	
Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
Nominal discharge current	Common mode: 10 kA (N/PE) Common mode: 10 kA (L/N)
Maximum discharge current	Differential mode: 20 kA L/N Differential mode: 20 kA N/PE
[Uc] maximum continuous operating voltage	Differential mode: 275 V L/N Differential mode: 275 V N/PE
Maximum [Up] voltage protection level	Differential mode <1.3 kV type 2 L/N
Local signalling	Green and red flag
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	8
Height	90 mm
Width	72 mm
Depth	66.2 mm
Colour	Grey (RAL 7035)
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal (downside) 535 mm² solid or flexible
 Tightening torque	3.5 N.m

Environment

Standards	IEC 61643-11
Product certifications	EAC GOST
IP degree of protection	IP20 on terminal:
Relative humidity	590 %
Operating altitude	2000 m
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-570 °C

Packing Units

Package 1 Weight	0.426 kg	
Package 1 Height	0.750 dm	
Package 1 width	0.800 dm	
Package 1 Length	1.030 dm	

Offer Sustainability

Green Premium product	
REACh Declaration	
Yes	
Compliant EU RoHS Declaration	
Yes	
Yes	
Yes	
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Product Environmental Profile	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	