




Ref.No.	Size mm
WSCS 20	20
WSCS 25	25
Colour : White / Black	




Ref.No.	Size mm
WBS 20	20
WBS 25	25
Colour : White / Black	




Ref.No.	Size
WBP-1S	1Gang
WBP-1	1Gang
WBP-2	2Gang
Colour : White	




Ref.No.	Size
WKOB-1	1Gang
WKOB-2	2Gang
WKOB-3	2x1Gang
Colour : White / Black	




Ref.No.	Length m	Diameter mm
WWP 4015	15	4.0
WWP 4030	30	4.0
WWP 4550	50	4.5
WWP 45100	100	4.5
Colour : White / Orange		



Ref.No.	W x L mm
WCTM 19	19 x 19
WCTM 28	28 x 28
Colour : White / Black	




Ref.No.	Cable Size mm
WEC 1.25	1.5
WEC 2	2.5
WEC 3.5	4
WEC 5.5	6
WEC 8	10
WEC 14	16
WEC 22	25 & 35
WEC 38	50
WEC 60	70
WEC 80	95
WEC 100	120
WEC 125	150
WEC 150	185
WEC 200	240
WEC 250	300
WEC 325	350
WEC 400	400
WEC 500	500
WEC 630	630
Colour : Red, Yellow, Blue, Black, Green	



Ref.No.	Size
PKOB-1A	1Gang
Colour : White / Black	



Ref.No.	L x W x H mm
WEB 442	110 x 110 x 60
WEB 444	110 x 110 x 110
WEB 643	155 x 115 x 80
WEB 644	155 x 115 x 110
WEB 863	215 x 150 x 80
WEB 864	215 x 150 x 110
WEB 883	215 x 215 x 80
WEB 884	215 x 215 x 110
WEB 1084	250 x 200 x 110
WEB 1086	250 x 200 x 160
WEB 1296	310 x 230 x 145
WEB 15127	390 x 310 x 180
Colour : Light Grey	



Ref.No.	Cable Diameter mm	Mounting Hole mm
WPG-07	3 - 6	13
WPG-09	4 - 8	16
WPG-11	5 - 10	19
WPG-13.5	7 - 12	20
WPG-16	10 - 14	23
WPG-21	13 - 18	29
WPG-29	18 - 25	37
WPG-36	22 - 32	48
WPG-42	30 - 38	54
WPG-48	34 - 44	60
WPG-63	42 - 50	73
Colour : Light Grey		

- ABS thermoplastic
- IP56 Dust/weatherproof
- High impact strength
- Temperature range from -5°C ~ +70°C
- Chemical resistance to aqueous acids, alkalis, seawater, concentrated phosphoric & hydrochloric acid

