TOA

THINNER 43

Technical Data Sheet



Rev. 1 10/2017

	Rev. 1 10/2017
FEATURES	
	: THINNER NO.43 is a high quality thinner for reducing or diluting the 2 pack polyurethane paint
	(Part A and Part B mixed).
	It is specially formulated to give the coating the optimum performance-promoting easy application,
	so that flows out smoothly without brushmark and developing maximum gloss and depth of finish film
	: It is suitable for reducing TOA HEAVYGUARD TOPGUARD or 2 pack polyurethane paint.
TECHNICAL INFORMATION	
Туре	: Thinner
Color	: Clear
Specific gravity	: 0.8 <u>+</u> 0.02
Flash point	: 26 °C
HANDLING AND STORAGE	
Storage condition	: The product must be stored in accordance with national regulations. Storage conditions are to keep
	the containers in a dry, cool, well ventilated space and away from source of heat and ignition.
Shelf life	: 60 months at 30–35 °C
	: The product must be stored in accordance with national regulations. Storage conditions are to keep
	the containers in a dry, cool, well ventilated space and away from source of heat and ignition.
	Containers must be kept tightly closed.
Package	: 1 Gallon and 1/4 Gallon
HEALTH AND SAFETY	
	: Please observe the precautionary notices displayed on the container. Use under well ventilated
	conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately
	be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and
	medical attention sought immediately.
	: For detailed information on the health and safety hazards and precautions for use of this product,
	we refer to the Safety Data Sheet.
DISCLAIMER	
	: The information in this data sheet is given to the best of our knowledge based on laboratory testing
	and practical experience. However, as the product is often used under conditions beyond our control,
	we cannot guarantee anything only the quality of the product itself. We reserve the right to change
	the given data without notice.