Technical Data Sheet



Rev.1 10/2017

| | Rev.1 10/2017 |
|-----------------------------------|--|
| FEATURES | |
| | TOA Enamel Thinner #21 is mixed organic solvents that suitable for TOA Wood Stain and Alkyd Base |
| | Enamel Paint. It provides excellent penetration and adhesion, good levelling, good flow that promotes |
| | a high gloss film. |
| | Recommend to use with TOA Wood Stain, Shark Wood Stain and Alkyd Base Enamel Paint. |
| TECHNICAL INFORMATION | |
| Туре | Mixed Organic Solvents |
| Color | Clear |
| Film appearance | - |
| Solid by volume | - |
| Solid by weight | - % |
| Flash point | 40.0 °C |
| Volatile organic compounds (VOCs) | - |
| Wet film thickness | - (non film) |
| Dry film thickness | - (non film) |
| Theoretical coverage. | - sq.m. / gallon / coat |
| | Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition |
| | method and technique; as well as the structure and dimensions of the object to be coated. |
| Touch dry (25-30°C) | - hours. |
| Recoat dry (25-30°C) | - hours. |
| Full cure (25-30°C) | - days. |
| REFERENCE STANDARD | |
| | - |
| APPLICATION | |
| Tools | - |
| Thinner No. | - |
| Dilution (%) | Mix with TOA Wood Stain, Shark Wood Stain and Alkyd Base Enamel Paint. |
| APPLICATION SYSTEM | |
| Surface Preparation | |
| Old surface | - |
| New surface | - |
| Coating system | |
| Primer | - |
| Topcoat | - |
| Recommendation | : The temperature of the substrate should be minimum 10°C and at least 3°C above the dew point of |
| | |
| | |
| | |
| | |
| Recommendation | : The temperature of the substrate should be minimum 10°C and at least 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate. Good ventilation is required in confined areas to ensure correct drying. |
| | |

Wood Coating Page: 2 TOA **TOA ENAMEL THINNER**

Technical Data Sheet



| o. 21 | |
|----------------------|--|
| | David 40/0047 |
| HANDLING AND STORAGE | Rev.1 10/2017 |
| Storage condition | : The product must be stored in accordance with national regulations. |
| Storage condition | Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. |
| | Containers must be kept tightly closed. |
| Shelf life | : 3 years. |
| HEALTH AND SAFETY | |
| | : Please observe the precautionary notices displayed on the container. Use under well ventilated |
| | conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately |
| | be removed with s uitable cleanser, soap and water. Eyes should be well flushed with water and |
| | medical attention sought immediately. |
| | : For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet. |
| DISCLAIMER | |
| | : The information in this data sheet is given to the best of our knowledge based on laboratory testing |
| | and practical experience. However, as the product is often used under conditions beyond our control, |
| | we cannot guarantee anything only the quality of the product itself. We reserve the right to change |
| | the given data without notice. |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |