

Specifications	Range	UT15C
LED AC/DC voltage indication (V)	12V	0~12V
	24V	17V±2V
	50V	35V±5V
	120V	80V±15V
	230V	165V±20V
	400V	300V±30V
	690V	510V±40V
Phase rotation test	Operating Voltage: 0V~690V	√
	Frequency: 50Hz~60Hz	
Single lead (L2) voltage detection	Operating Voltage: 0V~690V	√
	Frequency: 50Hz~400Hz	
Continuity test	Resistance: 0~100kΩ	√
	Beeper and LED light Indicator	
Polarity detection	Positive & Negative	√
Features		
Water-proof (IP65)		√
Auto range		√
Work light		√
Low battery indication	Short circuit two leads, LED and beeper off when the battery is low	√
LCD AC/DC voltage display	24V~690V	±(3%+5)
General Characteristics		
Power	1.5V battery (R03) × 2	
Display	UT15C- 23mm × 12mm	
Product color	Red and grey	
Product net weight	210g	
Product size (W x H x D)	275mm × 51mm × 30mm	
Standard accessories	Batteries	
Standard individual packing	Blister, English manual	
Standard quantity per carton	30 pcs	
Standard carton measurement	440mm × 395mm × 455mm (0.079CBM Per standard carton)	
Standard carton gross weight	17kg	