

Specifications	Range	UT202A+
AC current (A)	600A	$\pm(2\%+10)$
AC current frequency (Hz)	50Hz~100Hz	$\pm(1\%+5)$
AC voltage (V)	600V	$\pm(0.8\%+5)$
AC voltage frequency(Hz)	10Hz~10kHz	$\pm(1\%+5)$
DC voltage (A)	600V	$\pm(0.5\%+2)$
Resistance ( $\Omega$ )	60M $\Omega$	$\pm(0.8\%+2)$
Capacitance (F)	60mF	$\pm(4\%+5)$
Frequency (Hz)	10Hz~10MHz	$\pm(0.1\%+4)$
<b>Features</b>		
Display count		6000
Auto range		√
Jaw opening		28mm
True RMS		√
NCV		√
Live wire test		√
Continuity test		√
Diode		√
MAX/MIN		√
Relative mode		√
Data hold		√
Low battery indication		√
Auto power off		√
<b>General Characteristics</b>		
Power	1.5V battery (R03) x 2	
Display	37mm x 25mm	
Product color	Red and grey	
Product net weight	248g	
Product size	215mm x 63mm x 36mm	
Standard individual packing	Gift box, Carrying bag, English manual	
Standard quantity per carton	40pcs	
Standard carton measurement	485mm x 295mm x 385mm	
Standard carton gross weight	17.3kg	