



## Main

|                                 |   |
|---------------------------------|---|
| Range                           | Resi9   |
| Product name                    | Resi9 MP                                      |
| Product or component type       | Enclosure                                     |
| Enclosure type                  | Modular enclosure                             |
| Number of 18 mm modules per row | 12  |
| Number of horizontal rows       | 1   |
| Type of front cover             | Plain   |
| Width                           | 270 Mm wall:<br>294 Mm outside:               |
| Height                          | 228 Mm wall:<br>252 Mm outside:               |
| Depth                           | 18 Mm outside:<br>80 Mm wall:<br>98 Mm total: |

## Complementary

|                               |  |
|-------------------------------|--|
| Enclosure mounting            | Flush  |
| 9 mm pitches                  | 24   |
| Total number of 18 mm modules | 12   |
| [In] rated current            | 63 A   |
| Type of rail                  | 35 mm asymmetrical rail  |
| Mounting plate description    | Without mounting plate   |
| Cable entry                   | Pre-cutted holes   |
| Terminal block function       | Earth / neutral  |
| Number of terminal blocks     | 1 earth (screwed) with 8 outgoers<br>1 neutral (screwed) with 8 outgoers   |
| Distribution block outgoers   | 1 x 16 mm <sup>2</sup> for earth<br>1 x 16 mm <sup>2</sup> for neutral<br>3 x 6 mm <sup>2</sup> for earth<br>3 x 6 mm <sup>2</sup> for neutral<br>4 x 10 mm <sup>2</sup> for earth<br>4 x 10 mm <sup>2</sup> for neutral |
| Enclosure material            | Back part: technoplastic<br>Door: technoplastic<br>Front face: technoplastic   |
| Internal depth                | 76 Mm  |

|                |  |
|----------------|--|
| Colour         | Door: white (RAL 9003)<br>Front face: white (RAL 9003) |
| Market segment | Residential<br>Small commercial                        |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 61439-1<br>IEC 61439-3<br>IEC 60670-1<br>IEC 60670-24 |
| Quality labels                        | IMQ   |
| Fire resistance                       | Door: 650 °C<br>Back part: 650 °C<br>Front face: 650 °C   |
| IP degree of protection               | IP40  |
| IK degree of protection               | IK07  |
| Ambient air temperature for operation | -25...60 °C   |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 873.0 G  |
| Package 1 Height             | 9.8 Cm   |
| Package 1 width              | 29.4 Cm  |
| Package 1 Length             | 25.2 Cm  |
| Unit Type of Package 2       | P12      |
| Number of Units in Package 2 | 128      |
| Package 2 Weight             | 138.6 Kg |
| Package 2 Height             | 120 Cm   |
| Package 2 width              | 80 Cm    |
| Package 2 Length             | 120 Cm   |
| Unit Type of Package 3       | BB1      |
| Number of Units in Package 3 | 8        |
| Package 3 Weight             | 7.912 Kg |
| Package 3 Height             | 52 Cm    |
| Package 3 width              | 30 Cm    |
| Package 3 Length             | 40 Cm    |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| REACH Regulation            | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive           | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free                | Yes  |
| RoHS exemption information  | <a href="#">Yes</a>  |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>  |
| Halogen content performance | Halogen free product   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**