Product data sheet
Characteristics

A9XPH124
Acti9 - comb busbar - 1L - 18 mm pitch - 24 modules - 100A

Green Premium

Product availability: Stock - Normally stocked in distribution facility

Price*: 51.00 USD



Main

Range	Acti 9
Product or Component Type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L
Total number of 18 mm modules	24

Complementary

Number of ways	24 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	0.71 In (18 mm)
Connector type	Tooth
Distance between way	0.71 In (18 mm)
Marking	L
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC IEC 61439-2
Mounting Mode	Horizontal
Mounting location	Top or bottom tunnel type terminals Top or bottom double terminal
9 mm pitches	48
Width	16.93 In (430 mm)
Color	White RAL 9003)
Range compatibility	Acti9 iC60 Acti9 iK60 Acti9 iID Acti9 iID K Acti9 iSW Acti9 iSW-NA Multi 9 C60

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	1760 °F (960 °C) 30 s) IEC 60695-2-1
Pollution degree	3 IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	3606480485015
Nbr. of units in pkg.	1
Package weight(Lbs)	3.46 Oz (98.0 g)
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.20 In (0.5 cm)
Package 1 width	1.18 In (3 cm)
Package 1 Length	16.81 In (42.7 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	2.46 Lb(US) (1.118 kg)
Package 2 Height	2.44 In (6.2 cm)
Package 2 width	3.54 In (9 cm)
Package 2 Length	18.39 In (46.7 cm)
Unit Type of Package 3	S04
Number of Units in Package 3	100
Package 3 Weight	26.45 Lb(US) (11.996 kg)
Package 3 Height	11.81 In (30 cm)
Package 3 width	15.75 In (40 cm)
Package 3 Length	23.62 In (60 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised