Product data sheet Characteristics

EZ9S16240

Easy9 switch disconnector - 2P - 40 A - 400 V





Main

| Range | Easy9 | |
|---------------------------|--------------|--|
| Product or component type | Switch | |
| Device short name | Easy9 switch | |
| Switch application | Distribution | |
| Poles description | 2P | |
| Utilisation category | AC-22A | |
| Suitability for isolation | Yes | |

Complementary

| Complementary | | |
|---|--|--|
| [le] rated operational current | 40 A at 400 V 50/60 Hz | |
| [Ue] rated operational voltage | 400 V AC 50/60 Hz | |
| [lcm] rated short-circuit making capacity | 0.6 KA | |
| [lcw] rated short-time withstand current | 0.48 KA during 1 s | |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz | |
| [Uimp] rated impulse withstand voltage | 4 KV | |
| Control type | Toggle | |
| Local signalling | ON/OFF indication | |
| Contact position indicator | Yes | |
| Mounting mode | Clip-on | |
| Mounting support | DIN rail | |
| 9 mm pitches | 4 | |
| Height | 81 Mm | |
| Width | 36 Mm | |
| Depth | 66.5 Mm | |
| Colour | Grey | |
| Mechanical durability | 8500 Cycles | |
| Electrical durability | 1500 Cycles | |
| Connections - terminals | Tunnel type terminal (top or bottom) 135 mm² rigid Tunnel type terminal (top or bottom) 125 mm² flexible | |
| Tightening torque | 3.5 N.M | |
| | | |

Environment

| Standards | IEC 60947-3 |
|---------------------------------------|------------------------------|
| Product certifications | CE |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Tropicalisation | 2 |
| Ambient air temperature for operation | -555 °C |
| Ambient air temperature for storage | -570 °C |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 162.0 G |
| Package 1 Height | 7.7 Cm |
| Package 1 width | 3.6 Cm |
| Package 1 Length | 8.5 Cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 1152 |
| Package 2 Weight | 218.32 Kg |
| Package 2 Height | 80 Cm |
| Package 2 width | 80 Cm |
| Package 2 Length | 120 Cm |
| Unit Type of Package 3 | BB1 |
| Number of Units in Package 3 | 6 |
| Package 3 Weight | 1.034 Kg |
| Package 3 Height | 9 Cm |
| Package 3 width | 9 Cm |
| Package 3 Length | 23 Cm |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | ☑ REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EPEU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | ₫Yes |
| China RoHS Regulation | ☑ China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Product Life Status: Commercialised