Product data sheet Characteristics

A9XPH324

Acti9 - comb busbar - 3L - 18 mm pitch - 24 modules - 100A



Product availability: Stock - Normally stocked in distribution facility

Price*: 95.61 USD



Main

Range	Acti 9	=======================================
Product or Component Type	Comb busbar	
Accessory / separate part category	Connection accessory	
Lines description	3L	
Total number of 18 mm modules	24	;

Complementary

Complementary	
Number of ways	8 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	0.71 ln (18 mm)
Connector type	Tooth
Distance between way	2.13 ln (54 mm)
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC IEC 61439-2
Mounting Mode	Horizontal
Mounting location	Top or bottom tunnel type terminals Top or bottom double terminal
9 mm pitches	48
Width	16.93 In (430 mm)
Color	White RAL 9003)
Range compatibility	Acti9 iC60 Acti9 iK60 Acti9 iID Acti9 iID K Acti9 iSW Acti9 iSW Acti9 iSW-NA Multi 9 C60

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products with respect to the relevant specific user and products with respect to the relevant specific application or use thereof. It is the duty of any sub-user to rintegrator to perform the appropriate and compilete risk analysis, evaluation and relevant of the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	1760 °F (960 °C) 30 s) IEC 60695-2-1
Pollution degree	3 IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Ordering and shipping details

Category	00908-C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	3606480485053
Nbr. of units in pkg.	1
Package weight(Lbs)	8.18 Oz (232.0 g)
Returnability	Yes
Country of origin	DE

Packing Units

r acking critis	
Unit Type of Package 1	PCE
Package 1 Height	1.18 ln (3 cm)
Package 1 width	0.59 ln (1.5 cm)
Package 1 Length	16.93 ln (43 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Weight	24.25 Lb(US) (11.0 kg)
Package 2 Height	11.81 ln (30 cm)
Package 2 width	15.75 ln (40 cm)
Package 2 Length	23.62 ln (60 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	480
Package 3 Weight	319.67 Lb(US) (145.0 kg)
Package 3 Height	41.34 ln (105 cm)
Package 3 width	31.50 ln (80 cm)
Package 3 Length	47.24 ln (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	[™] China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.



Contractual warranty

Warranty 18 months

Product Life Status: Commercialised