# Product data sheet Characteristics

# **A9XPH424**

Acti9 - comb busbar - 3L+N - 18 mm pitch - 24 modules - 100 A



Product availability: Stock - Normally stocked in distribution facility

Price\*: 135.00 USD



#### Main

Range	Acti 9
Product or Component Type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Total number of 18 mm modules	24

#### Complementary

o o improvincintary	
Number of ways	6 ways N + 3 L
Poles configuration for 1 way	1 x 3P + N
	1 x 4P
Connection pitch	0.71 ln (18 mm)
Connector type	Tooth
Distance between way	2.83 ln (72 mm)
Marking	N L1 L2 L3
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC IEC 61439-2
Mounting Mode	Horizontal
Mounting location	Top or bottom tunnel type terminals
	Top or bottom double terminal
9 mm pitches	48
Width	16.93 ln (430 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not to be used for determining suitability or reliability of these products for specific user applications. First to the be used for determining suitability or reliability of the products with respect to the relevant specific application or use thereof. It is the duty of any sub-user to rintegrator to perform the appropriate and complete risk analysis, evaluation and respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

Color	White RAL 9003)	
Range compatibility	Acti9 iC60	
	Acti9 iK60	
	Acti9 iID	
	Acti9 iID K	
	Acti9 iSW	
	Acti9 iSW-NA	
	Multi 9 C60	

#### Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	1760 °F (960 °C) 30 s ) IEC 60695-2-1
Pollution degree	3 IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

### Ordering and shipping details

0 11 0	
Category	00908-C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	3606480485077
Nbr. of units in pkg.	1
Package weight(Lbs)	9.88 Oz (280.0 g)
Returnability	No
Country of origin	DE

#### **Packing Units**

i acking critis	
Unit Type of Package 1	PCE
Package 1 Height	2.20 ln (5.6 cm)
Package 1 width	3.31 ln (8.4 cm)
Package 1 Length	18.35 ln (46.6 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	35
Package 2 Weight	26.16 Lb(US) (11.866 kg)
Package 2 Height	11.81 ln (30 cm)
Package 2 width	15.75 ln (40 cm)
Package 2 Length	23.62 ln (60 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	420
Package 3 Weight	340.38 Lb(US) (154.392 kg)
Package 3 Height	41.34 ln (105 cm)
Package 3 width	31.50 ln (80 cm)
Package 3 Length	47.24 ln (120 cm)

## Offer Sustainability

•		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	☑ China RoHS Declaration	



Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Contractual warranty Warranty	18 months