Product data sheet Characteristics

MIP22104

Enclosure, Resi9 MP, flush mounting, 1 row of 4 modules, IP40, white door, 1 earth + 1 neutral terminal blocks





Main

| Range | Resi9 |
|---------------------------------|---|
| Product name | Resi9 MP |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Number of 18 mm modules per row | 4 |
| Number of horizontal rows | 1 |
| Type of front cover | Plain |
| Width | 126 Mm wall: 150 Mm outside: |
| Height | 228 Mm wall: 252 Mm outside: |
| Depth | 18 Mm outside: 80 Mm wall: 98 Mm total: |

Complementary

| Complementary | | |
|-------------------------------|---|--|
| Enclosure mounting | Flush | |
| 9 mm pitches | 8 | |
| Total number of 18 mm modules | 4 | |
| [In] rated current | 50 A | |
| Type of rail | 35 mm asymmetrical rail | |
| Mounting plate description | Without mounting plate | |
| Cable entry | Pre-cutted holes | |
| Terminal block function | Earth / neutral | |
| Number of terminal blocks | 1 earth (screwed) with 4 outgoers 1 neutral (screwed) with 4 outgoers | |
| Distribution block outgoers | 1 x 16 mm² for earth 1 x 16 mm² for neutral 1 x 6 mm² for earth 1 x 6 mm² for neutral 2 x 10 mm² for earth 2 x 10 mm² for earth | |
| Enclosure material | Back part: technoplastic Door: technoplastic Front face: technoplastic | |
| Internal depth | 76 Mm | |
| | | |

| Colour | Door: white (RAL 9003) Front face: white (RAL 9003) | |
|----------------|---|--|
| Market segment | Residential | |
| | Small commercial | |

Environment

| Z. T. T. G. T. T. G. T. | |
|---|--------------------|
| Standards | IEC 61439-1 |
| | IEC 61439-3 |
| | IEC 60670-1 |
| | IEC 60670-24 |
| Quality labels | IMQ |
| Fire resistance | Door: 650 °C |
| | Back part: 650 °C |
| | Front face: 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -2560 °C |
| | |

Packing Units

| i doking office | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 496.0 G |
| Package 1 Height | 9.5 Cm |
| Package 1 width | 15 Cm |
| Package 1 Length | 25 Cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 15 |
| Package 2 Weight | 8.076 Kg |
| Package 2 Height | 53 Cm |
| Package 2 width | 31 Cm |
| Package 2 Length | 41 Cm |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 240 |
| Package 3 Weight | 141.208 Kg |
| Package 3 Height | 118.5 Cm |
| Package 3 width | 80 Cm |
| Package 3 Length | 120 Cm |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|-----------------------------|--|--|
| REACh Regulation | ☑ REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | €Yes | |
| China RoHS Regulation | Ğ China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| Halogen content performance | Halogen free product | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| | |

| Product Life Status: | Commercialised | |
|----------------------|----------------|--|
| | | |

