

Commercial status

End-of-Sale Notice: DEC 15, 2021

Main

Range	Digilink
Product or component type	Patch cord
Cable shielding type	UTP
Colour tint	Blue

Complementary

Type of cable	4 twisted-pairs cable	
Communication network category	6	
Connector type	RJ45	
Material	PC (polycarbonate): plug	
AWG gauge	AWG 23 stranded cable	
Insulation resistance	>= 500 mOhm at 500 V DC	
Contacts material	Gold over nickel	
[ln] rated current	1.5 A	
Contact resistance	20 MOhm	
[Ue] rated operational voltage	< 72 V DC	
Cable length	5 M	

Environment

Standards	ANSI/TIA-568-C.2 Class E ISO/IEC 11801	
Product certifications	ETL verified	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	185.0 G	
Package 1 Height	2 Cm	
Package 1 width	27 Cm	
Package 1 Length	33 Cm	
Unit Type of Package 2	BAG	
Number of Units in Package 2	1	
Package 2 Weight	186.0 G	
Package 2 Height	2 Cm	
Package 2 width	27 Cm	
Package 2 Length	33 Cm	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interneted as a substitute for and is not to be used for determining suitability or reliability of these products with expect to the relevant specific application it is the douty of any sub user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitatives shall be responsible or liable for misuse of the information contained herein.

Unit Type of Package 3	S03	
Number of Units in Package 3	20	
Package 3 Weight	4.41 Kg	
Package 3 Height	30 Cm	
Package 3 width	30 Cm	
Package 3 Length	40 Cm	

Offer Sustainability

EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Product Life Status : End of commercialisation

DC6PCURJ05BLM may be replaced by any of the following products:



ACTPC6UUCM50BU

Patch cord, Actassi, Category 6, U/UTP, PVC, 5 m, blue Qty 1

Substitution date: |