



Commercial status

End-of-Sale Notice : DEC 15, 2021

 End-of-Sale Notice

Main

Range	Digilink
Product or component type	Patch cord
Cable shielding type	UTP
Colour tint	Grey

Complementary

Type of cable	4 twisted-pairs cable
Communication network category	6
Connector type	RJ45
Material	PC (polycarbonate): plug
AWG gauge	AWG 23 stranded cable
Insulation resistance	≥ 500 mOhm at 500 V DC
Contacts material	Gold over nickel
[In] rated current	1.5 A
Contact resistance	20 MOhm
[Ue] rated operational voltage	< 72 V DC
Cable length	5 M

Environment

Standards	ANSI/TIA-568-C.2 Class E ISO/IEC 11801
Product certifications	ETL verified

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	185.0 G
Package 1 Height	2 Cm
Package 1 width	27 Cm
Package 1 Length	33 Cm
Unit Type of Package 2	S03
Number of Units in Package 2	35
Package 2 Weight	6.96 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Unit Type of Package 3	P12
Number of Units in Package 3	560
Package 3 Weight	123.39 Kg
Package 3 Height	80 Cm
Package 3 width	80 Cm
Package 3 Length	120 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**

DC6PCURJ05GYM may be replaced by any of the following products:



ACTPC6UUCM50WE

Patch cord, Actassi, Category 6, U/UTP, PVC, 5 m, white

Qty 1

Substitution date: |