



Commercial status

End-of-Sale Notice : NOV 28, 2021

 End-of-Sale Notice

Main

Range of product	Digilink
Product or component type	Modular jack
Cable shielding type	UTP
Communication network category	6
Colour tint	Blue

Complementary

Connector type	RJ45
Type of footprint	Keystone
Insulation resistance	≥ 500 mOhm at 500 V DC
Minimum number of matings	750 Cycles
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Pulling force	140 N
Delay skew	2.5 Ns at 1...100 MHz
[In] rated current	1.5 A
Contact resistance	20 MOhm
[Ue] rated operational voltage	< 72 V DC

Environment

Flame retardance	V-0 conforming to UL 94
Product certifications	ETL verified
Standards	ISO/IEC 11801 class E ANSI/TIA-568-C.2 CENELEC EN 50173

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.0 G
Package 1 Height	1 Cm
Package 1 width	9 Cm
Package 1 Length	15 Cm
Unit Type of Package 2	S03
Number of Units in Package 2	400
Package 2 Weight	4.625 Kg
Package 2 Height	30 Cm

Package 2 width	30 Cm
Package 2 Length	40 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	500
Package 3 Weight	5470.0 G
Package 3 Height	24 Cm
Package 3 width	28 Cm
Package 3 Length	39 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. - Block**