# Product data sheet Characteristics

## EZAUX10

auxiliary switch AX, EasyPact EZC 100, EasyPact CVS 100BS, 1 common point changeover contact



### Main

Denote of another	F70400	
Range of product	EZC100	
Range	EasyPact	
Device short name	AX	
Product or component type	Switch	
Device application	Signalling	
Range compatibility	EZC circuit breaker	
Signal contacts composition	1 NO/NC	

#### Complementary

Auxiliary contacts type	Standard
[Ith] conventional free air thermal current	5 A
[le] rated operational current	AC-12: 3 A at 250 V AC 50/60 Hz
	AC-12: 5 A at 125 V AC 50/60 Hz
	AC-12: 5 A at 24 V AC 50/60 Hz
	AC-12: 5 A at 48 V AC 50/60 Hz
	AC-15: 2 A at 250 V AC 50/60 Hz
	AC-15: 3 A at 125 V AC 50/60 Hz
	AC-15: 5 A at 24 V AC 50/60 Hz
	AC-15: 5 A at 48 V AC 50/60 Hz
	DC-12: 0.2 A at 250 V DC
	DC-12: 0.4 A at 125 V DC
	DC-12: 2.5 A at 48 V DC
	DC-12: 4 A at 24 V DC
	DC-14: 0.2 A at 250 V DC
	DC-14: 0.4 A at 125 V DC
	DC-14: 1 A at 48 V DC
	DC-14: 3 A at 24 V DC
Minimum load	10 MA at 24 V
Auxiliary connection terminal	Lead wire

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	40.0 G	
Package 1 Height	2.5 Cm	
Package 1 width	7 Cm	
Package 1 Length	8.5 Cm	

## Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty 18 months

Product Life Status: Commercialised

