Product data sheet Characteristics

EZESHT200AC

shunt trip release SHT - 200..240 V AC - for EZ250





Main

Device short name	SHT
Product or component type	Voltage release
Device application	Control
Range compatibility	EasyPact EZC
Voltage release type	Shunt trip release
[Uc] control circuit voltage	200240 V AC 50/60 Hz

Complementary

Threshold tripping voltage	0.7 Un tripping	
Auxiliary connection terminal	Lead wire	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	70.0 G	
Package 1 Height	7 Cm	
Package 1 width	3 Cm	
Package 1 Length	9 Cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	35	
Package 2 Weight	2.937 Kg	
Package 2 Height	30 Cm	
Package 2 width	30 Cm	
Package 2 Length	40 Cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months
vvarianty	

