Product data sheet Characteristics

A9A26960

undervoltage release, Acti9, iMN, voltage release, 220...240 V AC





Main

Range	Acti 9	
Product or component type	Undervoltage release	
Device short name	IMN	
[Uc] control circuit voltage	220240 V AC 50/60 Hz	
Control type	Standard	
9 mm pitches	2	

Complementary

Range compatibility	Acti9 iC65	
	Acti 9 ARA	
	Acti9 iDPN Vigi	
	Acti9 iID	
	Acti9 iSW-NA	
	Acti 9 RCA	
	Acti 9 iDPN (China version)	
	Acti9 iC60 double terminals miniature circuit breaker	
	Acti 9 iC40	
Local signalling	Action indicator	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top and bottom: YES	
Width	18 Mm	
Colour	White	
Connections - terminals	Clamp terminal - 1 cable(s) 8 mm ² - rigid	
	Clamp terminal - 2 cable(s) 2.7 mm ² - rigid	
	Clamp terminal - 1 cable(s) 6 mm ² - flexible	
	Clamp terminal - 2 cable(s) 2.7 mm ² - flexible with cable end	
Tightening torque	1 N.M	
Compatibility code	IMN	

Environment

EN/IEC 60947-5-1	
2 conforming to EN/IEC 60947-5-1	
95 % at 55 °C	
-2550 °C	
-4085 °C	
	2 conforming to EN/IEC 60947-5-1 95 % at 55 °C -2550 °C

Packing Units

PCE
1
81.0 G
3 Cm
8 Cm
9.5 Cm
S03
72
6.864 Kg
30 Cm
30 Cm
40 Cm
BB1
8
707.0 G
8.7 Cm
10 Cm
26.7 Cm

Offer Sustainability

E DE ACh Deplacation	
REACh Declaration	
Compliant EEU RoHS Declaration	
Yes	
₫Yes	
☐ China RoHS Declaration	
☐ Product Environmental Profile	
End Of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	
----------	-----------	--

Product Life Status : Commercialised