

OPPLE
LIGHTING



Test Button
Press once a month

Leakage Propmt
Press it before closing



The indicator shows when power is on and change its range when power is off



Safety lock position to maintenance safety



Air guide channel for dust collection



Super wide handle for easy operation



High strength flame retardant shell



Circuit Breaker is used for short circuit, overload and leakage protection of single-phase and three-phase circuits below 125A in single-phase and three-phase circuits. It includes 1P, 2P, 3P, 4P, 1P+N and other mini circuit breakers and leakage protection circuit breakers.



1P



2P



3P



1P+N



2P

Description	Ways	Rated Current	Breaking Capacity	Width (mm)	Wire Connection	Wire Disconnected
ZB-63C16-1P-breaker	1P	16A	4500A	18	L	L
ZB-63C20-1P-breaker	1P	20A	4500A	18	L	L
ZB-63C32-1P-breaker	1P	32A	4500A	18	L	L
ZB-63C40-1P-breaker	1P	40A	4500A	18	L	L
ZB-63C63-1P-breaker	1P	63A	4500A	18	L	L
ZB-63C16-2P-breaker	2P	16A	4500A	36	L+N	L+N
ZB-63C20-2P-breaker	2P	20A	4500A	36	L+N	L+N
ZB-63C32-2P-breaker	2P	32A	4500A	36	L+N	L+N
ZB-63C40-2P-breaker	2P	40A	4500A	36	L+N	L+N
ZB-63C63-2P-breaker	2P	63A	4500A	36	L+N	L+N
ZB-63C63-3P-breaker	3P	63A	4500A	54	L+L+L	L+L+L
ZBLE-63C32-1P+N-leakage circuit breaker	1P+N	32A	4500A	53.5	L+N	L
ZBLE-63C40-1P+N-leakage circuit breaker	1P+N	40A	4500A	53.5	L+N	L
ZBLE-63C63-1P+N-leakage circuit breaker	1P+N	63A	4500A	53.5	L+N	L
ZBLE-63C32-2P-leakage circuit breaker	2P	32A	4500A	71.5	L+N	L+N
ZBLE-63C40-2P-leakage circuit breaker	2P	40A	4500A	71.5	L+N	L+N
ZBLE-63C63-2P-leakage circuit breaker	2P	63A	4500A	71.5	L+N	L+N