

# Product data sheet

Specifications



## Circuit breaker, ComPact NS1000N, 50kA/415VAC, Micrologic 2.0 trip unit, 1000A, fixed, 3 poles 3d

33472

### Main

Range	ComPact
Product name	ComPact NS
Range of product	ComPact NS630b...1600
Device short name	Compact NS1000N
Product or component type	Circuit breaker
Device application	Distribution
Number of poles	3P
Protected poles description	3D
(In) rated current up to 65 °C	1000 A at 50 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category B
[Icu] rated ultimate short-circuit breaking capacity	30 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 40 kA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Trip unit name	Micrologic 2.0
Trip unit technology	Electronic
Trip unit protection functions	LI
Control type	Rotary handle Toggle
Circuit breaker mounting mode	Fixed

### Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	30 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 40 kA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2

<b>[Icw] rated short-time withstand current</b>	19.2 kA 1 s conforming to IEC 60947-2
<b>Mechanical durability</b>	10000 cycles
<b>Electrical durability</b>	2000 cycles at 690 V In 4000 cycles at 690 V In/2 5000 cycles at 440 V In 6000 cycles at 440 V In/2
<b>Power losses</b>	22 W
<b>Mounting support</b>	Backplate
<b>Upside connection</b>	Front
<b>Downside connection</b>	Front
<b>Connection pitch</b>	70 mm
<b>Protection type</b>	L : for overload protection (long time) I : for instantaneous short-circuit protection
<b>Trip unit rating</b>	1000 A at 50 °C
<b>Long-time pick-up adjustment type Ir (thermal protection)</b>	Adjustable 9 settings
<b>[Ir] long-time protection pick-up adjustment range</b>	0.4...1 x In
<b>Long-time protection delay adjustment type tr</b>	Adjustable 9 settings
<b>[Tr] long-time protection delay adjustment range</b>	12.5...600 s at 1.5 x Ir 0.5...24 s at 6 x Ir 0.7...16.6 s at 7.2 x Ir
<b>Thermal memory</b>	20 mn
<b>Instantaneous protection pick-up adjustment type li</b>	Adjustable
<b>[li] instantaneous protection pick-up adjustment range</b>	1.5...10 x Ir
<b>Earth-leakage protection</b>	Without
<b>Zone selective interlocking ZSI</b>	Without
<b>Auxiliary contact composition</b>	1 NO/NC
<b>Local signalling</b>	4 LEDs (red) for fault indication 1 LED (yellow) for overload
<b>Width (W)</b>	210 mm
<b>Height (H)</b>	327 mm
<b>Depth (D)</b>	147 mm
<b>Net weight</b>	14 kg

## Environment

<b>Standards</b>	EN/IEC 60947-2
<b>Product certifications</b>	ASEFA ASTA
<b>Pollution degree</b>	3 conforming to IEC 60947
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to EN 50102
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-50...85 °C

Relative humidity	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	11.48 kg
Package 1 Height	30.0 cm
Package 1 width	40.0 cm
Package 1 Length	60.0 cm
Unit Type of Package 2	S04
Number of Units in Package 2	1
Package 2 Weight	12.246 kg
Package 2 Height	30.0 cm
Package 2 width	40.0 cm
Package 2 Length	60.0 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------